
PRODUCT LEAFLET · EDITION NOVEMBER 2026

Copper & Brass Sheet



Copper Cu-ETP and Cu-DHP



SHEET / PLATE

Copper Sheet and Plate


Cu-ETP CW004A **Cu-DHP** CW024A

TEMPER
Soft · Quarter-hard · Half-hard · Hard

STANDARD SHEET SIZES
660 × 2000 · 1000 × 2000 mm

THICKNESS AND CUT SIZES
0.50–40 mm. For sheet under 5 mm thick, the minimum cut size is 1000 × 1000 mm, or 660 × 500 mm from 660 mm wide sheet.

Sheet standard: EN 1652 · EN 13599 for electrical purposes (Cu-ETP only)



COIL

Copper Coil

Cu-ETP CW004A **Cu-DHP** CW024A

THICKNESS
0.05–1.00 mm

WIDTH
Up to 1000 mm

TEMPER
Soft · Quarter-hard · Half-hard · Hard

NARROW WIDTHS
Slit to the width you need (Slit Copper Strip), minimum 60 kg

Strip standard: EN 1652 · EN 13599 for electrical purposes (Cu-ETP only)



SLIT STRIP

Slit Copper Strip

Cu-ETP CW004A **Cu-DHP** CW024A

THICKNESS
0.05–1.00 mm

WIDTH
Slit to the width you need

TEMPER
Soft · Quarter-hard · Half-hard · Hard

ORDERING
Minimum 60 kg for custom sizes


Strip standard: EN 1652 · EN 13599 for electrical purposes (Cu-ETP only)

GRADE EQUIVALENTS · COPPER

Grades and international equivalents

GRADE	DESIGNATION / EN	DIN	UNS	BS	JIS	DENSITY
Cu-ETP	Cu-ETP · CW004A	2.0060	C11000	C101	C1100	8.9 g/cm³
Cu-DHP	Cu-DHP · CW024A	2.0090	C12200	C106	C1220	8.94 g/cm³

Brass CW508L (Ms63) and CW505L (Ms70)



SHEET / PLATE

Brass Sheet and Plate


MS63 CuZn37 · CW508L | **MS70** CuZn30 · CW505L

TEMPER
Soft · Half-hard · Hard

STANDARD SHEET SIZES
660 × 2000 · 660 × 3000 · 1000 × 2000 · 1000 × 3000 mm

THICKNESS AND CUT SIZES
0.50–50 mm. Custom sizes are supplied from stock or produced to order, depending on size and quantity. For sheet under 5 mm thick, the minimum cut size is 1000 × 1000 mm, or 660 × 500 mm from 660 mm wide sheet.

Sheet standard: EN 1652 · ASTM B36



COIL

Brass Coil

MS63 CuZn37 · CW508L | **MS70** CuZn30 · CW505L


THICKNESS
0.10–1.00 mm

WIDTH
Up to 660 mm

TEMPER
Soft · Half-hard · Hard

NARROW WIDTHS
Slit to the width you need (Slit Brass Strip), minimum 60 kg

Strip standard: EN 1652



SLIT STRIP

Slit Brass Strip

MS63 CuZn37 · CW508L | **MS70** CuZn30 · CW505L

THICKNESS
0.10–1.00 mm

WIDTH
Slit to the width you need

TEMPER
Soft · Half-hard · Hard

ORDERING
Minimum 60 kg for custom sizes

Strip standard: EN 1652

GRADE EQUIVALENTS · BRASS

Grades and international equivalents

GRADE	DESIGNATION / EN	DIN	UNS	BS	JIS	DENSITY
MS63	CuZn37 · CW508L	2.0321	C27200	CZ108	C2720	8.44 g/cm³
MS70	CuZn30 · CW505L	2.0265	C26000	CZ106	C2600	8.53 g/cm³

CONTACT

For quotations and information

Send us the product, grade, size and quantity. Drawings or specifications can be sent by WhatsApp or e-mail.

HEAD OFFICE · Çorlu / Tekirdağ
Zafer Mah. İmalat 8. Sk. No: 24, 59850 Çorlu / Tekirdağ, Türkiye
Tel +90 282 673 71 06
WhatsApp +90 530 671 13 78

BRANCH · İkitelli / Istanbul
İkitelli OSB Mah. Demirciler Sanayi Sitesi, B5 Blok No: 130, 34490 Başakşehir / Istanbul, Türkiye
WhatsApp +90 530 671 13 78

E-MAIL · WEB
info@pointmetal.com.tr
www.pointmetal.com.tr
Monday – Friday 08:00 – 18:00 · Saturday 08:00 – 14:00 · Sunday Closed

Full catalogue covering all product groups — www.pointmetal.com.tr/en/catalogue